



Cissbury Red Multi Stock A0767L

Declaration includes Special Shapes listed in BS4729 and Ibstock variants to Category II System 4

Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer: **Facing and rendered masonry, load bearing or non-loadbearing masonry structures including internal linings and partitions for building and civil engineering.**

U for use in Unprotected Masonry

Registered office
Ibstock Brick Limited. Leicester Road. Ibstock Leicestershire. LE67 6HS

Attestation of Conformity System 4

Declared Performance Essential Characteristics	Performance		Harmonised Technical Specification	The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer. Signed for and on behalf of the manufacturer by: Andy Batterham - Technical & Innovation Director Ibstock Brick Limited 
Dimensions and tolerance mm	215x102x65		BS EN771-1:2011/A1:2015	
	Tolerance	T2		
	Range	R1		
Configuration	Single Frog			
Group	HD units Group 1 Structural			
Flatness of bed faces	NPD			
Plane parallelism	NPD			
Compressive Strength (tested normal to the bed face of the unit) N/mm ²	Mean	25		
	Normalised	25.5		
	Category	Cat II		
Dimensional Stability mm/m	NPD			
Bond Strength fixed N/mm ²	0.15			
Active Soluble Salts	S2			
Reaction to Fire	Euro Class A1		Commission Decision 2000/605/EC	
Water absorption %	14		BS EN771-1:2011/A1:2015	
Water vapour permeability	5/10 mμ			
Direct airborne sound insulation	1520			
Thermal conductivity W/mk	0.88			
Durability against freeze thaw	F2			
Dangerous substances	NPD			

Data correct since: 01/02/2022
For data prior to this date please contact technical@ibstock.co.uk
Downloaded: 20/6/2024