

TECHNICAL DATA

EASYScape GRAVEL HOLD

Multipurpose binder fixes decorative stones and mulch in place



5 litre ready-to-use bottle

- Glues loose garden pebbles, gravel, stone, bark and mulch
- EASY to use pour on, spray on or mix in
- Resin binder coats stones in a protective sheen, leaving the surface permeable for water to go through
- For use on new or existing stones
- Suitable for pebbles and gravel sizes 4mm to 20mm diameter
- Water based and non-hazardous

NOTE: EASYScape GRAVEL HOLD is not designed to withstand excessive or prolonged foot traffic. Performance depends on gravel shape and size, depth of gravel and ground conditions. Not suitable for use by vehicles.

APPLICATION: USE NEAT AS SUPPLIED

- Shake well
- Always test a small hidden area before use to ensure compatibility and that the finished result is acceptable
- Pebbles and gravel must be washed to remove any dust and allowed to dry before applying GRAVEL HOLD

GRAVEL MIX METHOD

Mix GRAVEL HOLD with your stones until evenly coated, at a ratio of 1L GRAVEL HOLD to 10kg stone. Spread to the desired thickness and tamper to settle the gravel in place.

The mixing method leaves the strongest finish, especially if the surface is to receive any light foot traffic.

For best results, allow to dry, then apply a light coating to the gravel using a garden sprayer. Repeat this process if some stones are still loose*.

GRAVEL & MULCH SPRAY-ON METHOD

GRAVEL HOLD can be applied using a garden sprayer. Apply a generous, even coat across the surface at a rate of 1m² per litre. Lightly rake and spray again. Leave to dry. Repeat after 24 hours for extra strength*.

GRAVEL & MULCH POUR-ON METHOD

GRAVEL HOLD can be poured from a watering can, ensuring your stones are evenly coated. This method can be useful for smaller areas of gravel. Make sure you use a watering can with a steady flow that disperses the liquid evenly across the stones or mulch. The surface should be lightly raked and turned over for best results*.

*NOTE: GRAVEL HOLD is air drying, so application of excessive amounts will leave the surface wet and unbonded for a longer period. Drying time is approximately 24 hours - longer in colder weather.

STORAGE

Product should be stored in original container out of direct sunlight. Unopened shelf-life is 12 months from date of manufacture.

DISPOSAL

Dispose of unused product at a local waste recycling centre. Do not re-use empty containers.

Empty bottles can be recycled at a local waste recycling centre.

HEALTH & SAFETY

- Keep out of reach of children
- Do not get in eyes, on skin, or on clothing
- Wear protective gloves/protective clothing/eye protection/face protection
- IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Seek medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention if you feel unwell

Contains: 1,2-benzisothiazolin-3-one(2634-33-5), reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2h-isothiazol-3-one(55965-84-9). May produce an allergic reaction. Safety data sheet available on request.

DISCLAIMER

If used in accordance with the instructions, *EASYS* cape GRAVEL HOLD should produce results as described, but no guarantees are given or implied. Neither the manufacturer nor supplier accept any liability for markings or changes in appearance of the material on which it is used.

Version: 0725